

Docket No. 338520-5174
US Appln. No. 10/008,509

IN THE CLAIMS

1. (currently amended) A segmented arm support apparatus for attachment to a surgical retractor, comprising:

an articulating arm having a plurality of segments, each segment of the same size and shape, each segment having an outer wall and an inner surface with a passage extending through each segment, the outer wall of a first segment in mating relationship with the inner surface of a second segment, each segment being formed of a material with high stiffness coated with a high friction plating material;

a cable extending through the passage of each segment;

a manual device for variably tightening the cable, thereby causing the mating segments to be brought into tight frictional engagement and compressing the plating material; and

a tissue stabilization device attached to the articulating arm, the stabilization device being lockable upon tightening the cable, wherein the stabilization device is removably attached to the segmented arm support apparatus, and

further including a movable socket to receive the stabilization device, wherein the movable socket is slidable along a plunger attached to an end of the cable and wherein the movable socket is biased against the plunger by a spring.

2. (original) The segmented arm support apparatus of claim 1, wherein each segment is defined by a convex outer wall and a concave inner surface.

3. (original) The segmented arm support apparatus of claim 2, wherein the convex outer wall of the first segment engages the concave inner surface of the second segment.

4. (previously canceled)

Docket No. 338520-5174
US Appl. No. 10/008,509

5. (original) The segmented arm support apparatus of claim 1, wherein the mating relationship exists between each segment.
6. (original) The segmented arm support apparatus of claim 1, wherein the high friction plating material is softer than the material with high stiffness.
7. (original) The segmented arm support apparatus of claim 1, wherein the high friction plating material is selected from the group consisting of nickel, gold, silver, copper, tin, and an elastomer.
8. (original) The segmented arm support apparatus of claim 1, wherein the high friction plating material comprises nickel.
9. (original) The segmented arm support apparatus of claim 1, wherein during tightening of the cable, the high friction plating material of adjacent segments frictionally engages.
10. (previously canceled)
11. (previously canceled)
12. (canceled) The segmented arm support apparatus of claim 1, wherein the movable socket is slidable along a plunger attached to an end of the cable.
13. (canceled) The segmented arm support apparatus of claim 12, wherein the movable socket is biased against the plunger by a spring.
14. (original) The segmented arm support apparatus of claim 1, and further including a mounting block for attachment to a retractor.

Docket No. 338520-5174
US Appln. No. 10/008,509

15. (original) The segmented arm support apparatus of claim 14, the mounting block including a lever for positioning a cam to engage the retractor.

16. (currently amended) A method for stabilizing a localized area of tissue on a patient, comprising the steps of.

providing a segmented arm support apparatus including an articulating arm with a plurality of segments, each segment having the same size and shape, each segment having an outer wall, an inner surface, and a passage for receiving a cable, the outer wall of a first segment in mating relationship with the inner surface of a second segment, each segment being formed of a material of high stiffness coated with a plating material, a cable extending through the passage of each segment and a manual device for variably tightening the cable, thereby causing the mating segments to be brought into tight frictional engagement and compressing the plating material; and

providing a stabilization device attached to the articulating arm; and
tightening the cable so that the plating material of the first and second segments frictionally engages, thereby causing the stabilization device to lock, wherein the stabilization device is removably attached to the segmented arm support apparatus, and

further providing a movable socket to receive the stabilization device; and
further including a step of replacing the stabilization device by loosening the cable and removing the stabilization device from the movable socket wherein the moveable socket is biased against a plunger housing an end of the cable.

17. (previously canceled)

18. (original) The method of claim 16, wherein the plating material is selected from the group consisting of nickel, gold, silver, copper, tin, and an elastomer.

19. (original) The method of claim 16, wherein the plating material comprises nickel.

20. (previously canceled)

Docket No. 338520-5174
US Appln. No. 10/008,509

21. (canceled) The method of claim 16, and further including a step of replacing the stabilization device by loosening the cable and removing the stabilization device from a socket.

22. (canceled) The method of claim 21, wherein the socket is biased against a plunger housing an end of the cable.

23. (original) The method of claim 16, and further including a step of mounting the segmented arm support apparatus on a retractor.

24. (original) The method of claim 23, wherein the mounting step includes manually rotating a lever connected with a cam that attaches to the retractor.